


HMEC



Shaft diameter	Dimensions					Load rating		Limiting speed min ⁻¹	Reference speed	Code Bearing HMEC	Mass ≈ kg
	d	D	B	C	T	dyn. C	stat. Co				
	mm					kN					
105	105	145	25	20	25	129	220	4500	2400	32921	1.15
	105	160	35	26	35	204	335	4300	2400	32021X	2.33
	105	160	43	34	43	265	450	4300	2200	33021	3.34
	105	190	36	30	39	280	365	4000	2600	30221A	4.23
	105	190	50	43	53	380	550	3600	2200	32221A	6.07
	105	225	77	63	81.5	670	930	3000	2000	32321A	15.1
110	110	170	38	29	38	240	400	4000	2400	32022X	3.07
	110	170	47	37	47	300	520	4300	1500	33022	4.16
	110	200	38	32	41	315	415	3600	2400	30222A	5.23
	110	200	53	46	56	415	600	3400	2200	32222A	7.35
	110	240	50	42	54.5	480	585	2800	2200	30322A	11.1
	110	240	57	38	63	465	585	2800	2200	31322X	12.3
	110	240	80	65	84.5	735	1020	2800	1800	32322A	19.1
120	120	165	29	23	29	176	310	4000	2200	32924	1.82
	120	170	25	19.5	27	156	245	4000	2000	T4CB120	1.97
	120	180	38	29	38	250	425	3600	2200	32024X	3.28
	120	180	48	38	48	310	560	3600	1900	33024	4.55
	120	215	40	34	43.5	340	455	3000	2200	30224A	6.73
	120	215	58	50	61.5	490	735	3000	1900	32224A	9.28
	120	260	55	46	59.5	560	710	2600	1900	30324A	14.3
	120	260	62	42	68	540	695	2600	1900	31324X	15.4
	120	260	86	69	90.5	670	965	2600	1800	32324	21.1
	130	130	180	32	25	32	208	375	3600	2000	32926
130		185	27	21	29	183	280	3400	1900	T4CB130	2.55
130		200	45	34	45	335	560	3000	1900	32026X	5.02