


Taper Roller Bearing (metric size)



Shaft diameter	Dimensions					Load rating		Limiting speed	Reference speed	Code bearing HMEC	Mass ≈
	d	D	B	C	T	dyn. C	stat. Co				
	mm					kN	min ⁻¹				
130	130	230	40	34	43.75	360	480	2800	2000	30226A	7.08
	130	230	64	54	67.75	570	865	2800	1800	32226A	11.7
	130	280	58	49	63.75	600	750	2600	1800	30326	17.2
	130	280	66	44	72	610	800	2400	1700	31326X	18.8
	130	280	93	78	98.75	830	1120	2600	1700	32326	28.9
140	140	190	32	25	32	216	400	3400	1800	32928	2.62
	140	195	27	21	29	193	310	3000	1800	T4CB140	2.3
	140	210	45	34	45	345	610	2800	1700	32028X	5.9
	140	250	42	36	45.75	425	570	2600	1800	30228A	8.48
	140	250	68	58	71.75	655	1000	2600	1600	32228A	14
	140	300	62	53	67.75	585	735	2400	1800	30328	20.5
	140	300	70	47	77	695	900	2400	1600	31328X	23.4
	140	300	102	85	107.7	1160	1700	2400	1300	32328A	37.8
150	150	210	38	30	38	285	500	2800	1700	32930	3.9
	150	225	48	36	48	390	695	2600	1600	32030X	6.46
	150	270	45	38	49	475	640	2600	1700	30230A	11.1
	150	270	73	60	77	750	1160	2600	1400	32230A	18.5
	150	320	65	55	72	800	1020	2200	1500	30330A	25.5
	150	320	75	50	82	780	1020	2200	1500	31330X	30.8
	150	320	108	90	114	1320	1930	2200	1200	32330A	46.1
160	160	220	38	30	38	285	500	2600	1600	32932	4.17
	160	240	51	38	51	425	750	2600	1500	32032X	7.8
	160	290	48	40	52	405	585	2400	1700	30232	13.8
	160	290	80	67	84	880	1400	2400	1300	32232A	23.8
	160	340	68	58	75	880	1120	2200	1400	30332A	29.9