


HMEC



Dimensions					Load rating		Limiting speed		Code bearing HMEC		Mass m_s kg	
d	D	T	B	C	d ₁ C	stat. Co	min ⁻¹	(Grease) (OR)	(CONE) (CUP)	(CONE) (CUP)		
mm					kN							
72.628	24.608	24.257	17.462	60000	58000	5900	7500	4126	4126B	0.295	0.177	
73.025	22.225	22.225	17.462	54500	64500	5300	7100	62872	62820	0.321	0.16	
28.000	50.292	14.224	14.732	10.668	20800	34000	7100	8600	L45449	L45410	0.079	0.036
28.367	66.421	23.812	23.433	19.05	69000	73000	6000	9000	2096	2031	0.242	0.165
30.000	62.00	16.002	16.586	14.298	37800	33800	6300	8500	17118	17244	0.136	0.091
62.00	19.05	20.638	14.298	46000	53000	6000	8000	15117	15245	0.169	0.061	
63.50	20.638	20.638	15.875	46000	53000	6000	8000	15117	15245	0.169	0.113	
72.00	18.07	18.023	15.875	53000	55600	5000	7500	20118	20263	0.229	0.163	
30.112	62.00	16.05	20.638	14.298	46000	53000	6000	8000	15116	15245	0.169	0.061
30.162	58.738	14.691	15.08	16.716	28800	33600	6000	8000	06118	06221	0.12	0.067
68.262	22.225	22.225	17.462	65500	70800	6300	7500	M86043	M86010	0.263	0.146	
69.85	23.812	23.357	19.05	71000	84000	6600	7600	2558	2523	0.297	0.169	
69.85	23.812	23.357	19.05	71000	84000	6600	7300	2559	2523	0.289	0.169	
76.00	24.038	24.074	16.670	67600	69600	5000	6700	43118	43330	0.383	0.145	
30.212	62.00	19.05	20.638	14.298	46000	53000	6000	8000	15116	15245	0.169	0.061
62.00	19.05	20.638	14.298	46000	53000	6000	8000	15120	15245	0.169	0.061	
62.00	19.05	20.638	14.298	46000	53000	6000	8000	15119	15245	0.169	0.061	
30.900	64.292	21.433	21.433	18.67	21000	64200	8000	M86048	M86016	0.276	0.128	
31.750	58.738	14.694	15.08	16.716	28800	33600	6000	8000	06125	06231	0.113	0.067
96.131	15.875	16.704	11.831	34500	41000	6300	8800	L450148	L450148	0.127	0.062	
62.00	18.381	19.05	14.298	46000	53000	6000	8000	15123	15245	0.165	0.061	