

HMEC



Dimensions					Load rating		Limiting speed		Code		Mass	
d	D	T	B	C	dyn. C	stat. Co	min <sup>-1</sup>	bearing	HMEC	(CONE)	(CUP)	kg
mm					kN		(Gross)	(IQR)	(CONE)	(CUP)	(CONE)	(CUP)
165,00	27,00	35,00	29,00	130000	192000	3400	4900	24000000	24000000	1,01	0,523	
50,500	80,962	18,258	18,258	14,268	53000	81000	4300	5600	L305649	L305610	0,239	0,119
52,55	23,522	22,225	18,542	71000	96000	4300	5600	L160690	L160691A	0,303	0,158	
52,931	21,129	22,225	18,51	71000	96000	4300	5600	L160690	L160691Z	0,304	0,14	
85,00	17,462	17,462	13,495	48500	63000	4300	5600	18790	18720	0,239	0,136	
85,235	19,05	18,263	12,70	42500	54000	4000	5300	16200	16337	0,268	0,136	
88,90	20,838	22,225	16,513	73000	85000	4000	5600	368A	362A	0,338	0,166	
88,90	20,838	22,225	16,513	75000	85000	4000	5600	368	362A	0,341	0,160	
92,075	24,608	25,40	19,845	84500	117000	4000	5300	28580	28520	0,48	0,247	
93,294	20,162	20,302	23,812	100000	130000	3800	5300	3775	3730	0,568	0,297	
93,294	20,162	20,302	23,812	100000	130000	3800	5300	3780	3730	0,565	0,297	
95,25	27,783	28,575	22,225	110000	144000	3800	5300	33889	33821	0,601	0,287	
101,60	31,75	31,75	25,40	118000	150000	3800	5000	49585	49520	0,744	0,388	
101,60	34,025	36,068	28,988	137000	169000	3800	5000	529	522	0,822	0,416	
101,60	34,025	36,068	28,988	137000	169000	3800	5000	529A	522	0,819	0,416	
104,775	36,513	36,513	28,575	138000	180000	3400	4900	1160000	1160000	0,882	0,508	
104,775	36,512	36,512	28,575	138000	180000	3400	4900	1160000	1160000	0,893	0,502	
108,985	34,025	35,512	28,988	148000	181000	3800	4800	55200	55400	0,943	0,594	
111,125	30,162	26,959	23,838	113000	152000	3000	4300	55200C	55437	0,845	0,514	
111,125	30,162	26,959	23,838	92500	119000	2300	4300	55200	55437	0,767	0,514	
123,825	36,512	30,791	25,40	162000	199000	2800	4000	72200C	72487	1,33	0,79	
123,825	36,512	30,791	25,40	143000	160000	3000	4000	72200	72487	1,22	0,79	
127,00	44,45	44,45	34,925	199000	258000	3000	4000	65200	65500	1,86	1,03	