


HMEC



| Dimensions | | Load rating | | Limiting speed | | Code bearing | | Mass | |
|------------|---------|-------------|--------|----------------|--------|--------------|------------------|---------------------------------|---------------|
| d | D | T | B | C | dyn. C | stat. Co | mm ⁻¹ | HMEC | kg |
| mm | | | | | kN | | (Grease) (Oil) | (CONE) (CLIP) | (CONE) (CLIP) |
| 96.838 | 21.50 | 21.348 | 15.875 | 80500 | 100000 | 3600 | 5000 | 387 382A | 0.423 0.179 |
| 96.838 | 25.40 | 21.348 | 20.275 | 80500 | 100000 | 3600 | 5000 | 387A 382S | 0.42 0.249 |
| 96.425 | 21.00 | 21.848 | 17.828 | 80596 | 100000 | 3600 | 5000 | 387A 382 | 0.42 0.238 |
| 104.775 | 30.182 | 29.317 | 24.926 | 118000 | 149000 | 3400 | 4800 | 469 453X | 0.802 0.376 |
| 104.775 | 30.182 | 29.317 | 24.926 | 118000 | 149000 | 3400 | 4800 | 462 453X | 0.804 0.376 |
| 104.775 | 30.182 | 30.858 | 23.812 | 130000 | 170000 | 3400 | 4800 | 45289 45270 | 0.752 0.347 |
| 104.775 | 30.182 | 30.858 | 23.812 | 130000 | 170000 | 3400 | 4800 | 45289 4527X | 0.76 0.35 |
| 122.233 | 33.338 | 31.75 | 23.812 | 135000 | 156000 | 3000 | 4000 | 66587 66520 | 1.14 0.558 |
| 123.825 | 36.512 | 32.791 | 25.40 | 162000 | 180000 | 2900 | 4000 | 72279C 72487 | 1.10 0.70 |
| 123.825 | 38.10 | 36.678 | 30.162 | 161000 | 221000 | 3000 | 4000 | 5568 552A | 1.41 0.764 |
| 140.03 | 36.512 | 33.236 | 23.52 | 162000 | 183000 | 2900 | 3800 | 78225 78551 | 1.67 0.826 |
| 144.983 | 38.00 | 33.236 | 23.027 | 152000 | 183000 | 2900 | 3800 | 78225 78571 | 1.68 1.06 |
| 149.225 | 53.975 | 64.229 | 44.465 | 287000 | 410000 | 2600 | 3400 | 6455 6420 | 3.49 1.63 |
| 67.631 | 96.838 | 21.00 | 21.948 | 15.875 | 80500 | 100000 | 3600 | 388A 382A | 0.416 0.179 |
| 68.738 | 112.712 | 33.338 | 30.048 | 26.968 | 120000 | 173000 | 3300 | 3981 3926 | 0.899 0.541 |
| 60.000 | 66.00 | 34.00 | 34.00 | 16.00 | 86600 | 126000 | 3600 | 39236 39412 | 0.859 0.186 |
| 104.775 | 21.433 | 22.00 | 15.875 | 83600 | 107000 | 3400 | 4500 | 397 394A | 0.642 0.263 |
| 116.00 | 22.00 | 21.998 | 18.824 | 85600 | 113000 | 3200 | 4300 | 397 394A | 0.642 0.263 |
| 122.238 | 33.338 | 31.75 | 23.812 | 135000 | 156000 | 3000 | 4000 | 66585 66520 | 1.07 0.558 |
| 80.323 | 100.00 | 25.40 | 25.40 | 18.843 | 91000 | 129000 | 3400 | 28985 28921 | 0.538 0.232 |
| 101.06 | 25.40 | 25.40 | 18.843 | 91000 | 129000 | 3400 | 4500 | 28985 28926 | 0.538 0.272 |
| 122.238 | 38.10 | 36.678 | 30.162 | 161000 | 221000 | 3000 | 4000 | 558 553X | 1.31 0.692 |
| 122.238 | 38.10 | 38.264 | 29.718 | 188000 | 243000 | 3000 | 4000 | H9212844 H9212810 | 1.43 0.804 |