


HMEC



Dimensions					Load rating		Limiting speed		Code bearing		Mass	
d	D	T	B	C	dyn. C	stat. Co	min ⁻¹		HMEC		≈	
mm					kN		(Grease)	(Oil)	(CONE)	(CUP)	(CONE)	(CUP)
130.175	41.275	41.275	31.75	195000	263000	2800	3800	645	633	1.49	0.712	
136.525	41.275	41.275	31.75	195000	263000	2800	3800	644	632	1.5	1.04	
136.525	41.275	41.275	31.75	229000	297000	2600	3600	H414249	H414210	1.83	0.796	
136.525	46.038	46.038	36.512	233000	370000	2600	3400	H715345	H715311	2.15	0.961	
73.025	112.712	25.40	25.40	19.05	96000	152000	2800	4000	29685	29620	0.62	0.273
117.475	30.162	30.162	23.812	119000	179000	3000	4000	33287	33462	0.746	0.442	
127.00	36.512	36.17	28.575	166000	234000	2800	3800	567	563	1.17	0.655	
146.05	41.275	41.275	31.75	207000	296000	2400	3200	657	653	2.24	0.891	
149.225	53.975	54.229	44.45	287000	410000	2600	3400	6460	6420	2.8	1.63	
73.817	127.00	36.512	36.17	28.575	166000	234000	2800	3800	568	563	1.15	0.655
74.612	150.00	41.275	41.275	31.75	207000	296000	2400	3200	658	653	2.37	0.932
75.000	115.00	25.00	25.00	19.00	101000	150000	3000	4000	JLM714149	JLM714110	0.638	0.272
120.00	31.00	29.50	25.00	129000	198000	2800	3800	JM714249	JM714210	0.863	0.436	
145.00	51.00	51.00	42.00	287000	410000	2600	3400	JH415647	JH415610	2.64	1.19	
76.200	121.442	24.608	23.012	17.462	89000	124000	2800	3800	34300	34478	0.65	0.316
127.00	30.162	31.00	22.225	134000	195000	2800	3800	42687	42620	1.03	0.438	
127.00	36.162	31.001	22.225	134000	195000	2800	3800	42688	42620	1.01	0.438	
133.35	33.338	33.338	26.195	154000	237000	2600	3600	47680	47620	1.39	0.577	
135.732	44.45	46.101	34.925	216000	340000	2600	3600	5760	5735	1.86	0.887	
136.525	30.162	29.769	22.225	130000	192000	2600	3400	495A	493	1.27	0.55	
136.525	30.162	29.769	22.225	130000	192000	2600	3400	495AX	493	1.26	0.55	
139.992	36.512	36.098	28.575	175000	260000	2600	3400	575	572	1.61	0.788	
149.225	53.975	54.229	44.45	287000	410000	2600	3400	6461	6420	2.64	1.63	