



| Shaft diameter | Dimensions | | | | Load rating | | Limiting speed | Code bearing | Mass |
|----------------|------------|-----|----|--------------------|-------------|----------|-------------------|-----------------|-------|
| | d | D | B | r _{s min} | dyn. C | stat. Co | | | |
| | mm | | | | kN | | min ⁻¹ | HMEC | ≈ |
| | | | | | | | | | kg |
| 75 | 75 | 105 | 16 | 1 | 24.40 | 22.60 | 7100 | 6915 | 0.364 |
| | 75 | 105 | 16 | 1 | 24.40 | 22.60 | 6000 | 6915.ZZ | 0.364 |
| | 75 | 115 | 13 | 0.6 | 28.5 | 27 | 13000 | 16015 | 0.463 |
| | 75 | 115 | 20 | 1.1 | 39 | 33.5 | 13000 | 6015 | 0.654 |
| | 75 | 115 | 20 | 1.1 | 39 | 33.5 | 5600 | 6015.ZZ | 0.676 |
| | 75 | 115 | 20 | 1.1 | 39 | 33.5 | 3800 | 6015.2RS | 0.678 |
| | 75 | 130 | 25 | 1.5 | 65.5 | 49 | 11000 | 6215 | 1.18 |
| | 75 | 130 | 25 | 1.5 | 65.5 | 49 | 4800 | 6215.ZZ | 1.21 |
| | 75 | 130 | 25 | 1.5 | 65.5 | 49 | 3200 | 6215.2RS | 1.21 |
| | 75 | 160 | 37 | 2.1 | 114 | 76.5 | 9500 | 6315 | 3.18 |
| | 75 | 160 | 37 | 2.1 | 114 | 76.5 | 4000 | 6315.ZZ | 3.23 |
| | 75 | 190 | 45 | 3 | 132 | 96.5 | 8500 | 6415M | 7.08 |
| 80 | 80 | 100 | 10 | 0.6 | 12.70 | 14.50 | 7100 | 6816 | 0.151 |
| | 80 | 100 | 10 | 0.6 | 12.70 | 14.50 | 6000 | 6816.ZZ | 0.151 |
| | 80 | 110 | 16 | 1 | 25.00 | 24.00 | 6700 | 6916 | 0.391 |
| | 80 | 110 | 16 | 1 | 25.00 | 24.00 | 5600 | 6916.ZZ | 0.391 |
| | 80 | 110 | 16 | 1 | 25.00 | 24.00 | 3200 | 6916.2RS | 0.391 |
| | 80 | 125 | 14 | 0.6 | 32 | 31 | 13000 | 16016 | 0.609 |
| | 80 | 125 | 22 | 1.1 | 47.5 | 40 | 12000 | 6016 | 0.867 |
| | 80 | 125 | 22 | 1.1 | 47.5 | 40 | 5000 | 6016.ZZ | 0.889 |