



HMEC



HK



BK

Shaft diameter	Dimensions					Load ratings		Speed ratings		appropriate inner ring	Code bearing HMEC	Weight ≈ kg
	F _w	D	B	t	r ₁ , r ₂ min	dyn. C	stat. Co	min ⁻¹				
	mm					kN		ng grease	ng Oil			
9	9	13	12	10.4	0.4	5.4	6.8	15000	24000	IR 6x9x12	BK 0912	0.005
10	10	14	10	-	0.4	4.55	5.7	14000	22000	IR 7x10x10.5	HK 1010	0.004
	10	14	10	8.4	0.4	4.55	5.7	14000	22000	IR 7x10x10.5	BK 1010	0.004
	10	14	12	-	0.4	5.6	7.35	14000	22000	IR 7x10x12	HK 1012	0.005
	10	14	12	10.4	0.4	5.6	7.35	14000	22000	IR 7x10x12	BK 1012	0.005
	10	14	15	-	0.4	7.1	10	14000	22000	IR 7x10x16	HK 1015	0.006
	10	14	15	13.4	0.4	7.1	10	14000	22000	IR 7x10x16	BK 1015	0.006
12	12	16	10	-	0.4	4.75	6.3	12000	19000	IR 8x12x10.5	HK 1210	0.005
	12	16	10	8.4	0.4	4.75	6.3	12000	19000	IR 8x12x10.5	BK 1210	0.005
	12	18	12	-	1	6.3	7.35	12000	19000	IR 8x12x12.5	HK 1212	0.01
	12	18	12	9.3	1	6.55	7.8	12000	19000	IR 8x12x12.5	BK 1212	0.011
13	13	19	12	-	1	6.8	8.5	11000	18000	IR 10x13x12.5	HK 1312	0.012
	13	19	12	9.3	1	6.8	8.5	11000	18000	IR 10x13x12.5	BK 1312	0.012
14	14	20	12	-	1	6.8	8.5	10000	17000	IR 10x14x12	HK 1412	0.012
	14	20	12	9.3	1	6.8	8.5	10000	17000	IR 10x14x12	BK 1412	0.012
15	15	21	12	-	1	7.1	9.3	9500	16000	IR 12x15x12.5	HK 1512	0.012
	15	21	12	9.3	1	7.1	9.3	9500	16000	IR 12x15x12.5	BK 1512	0.015
	15	21	16	-	1	10.2	14.6	9500	16000	IR 12x15x16.5	HK 1516	0.018
	15	21	16	13.3	1	10.2	14.6	9500	16000	IR 12x15x16.5	BK 1516	0.019
	21	21	22	-	1	12.9	19.6	9500	16000	IR 12x15x22.5	HK 1522	0.024