



**Drawn Cup Needle Roller Bearings
with open end
Series HK
with closed end
series B**



HK



BK

Shaft diameter	Dimensions					Load ratings		Speed ratings		appropriate inner ring	Code bearing HMEC	Weight ≈ kg
	F _w	D	B	t	r ₁ , r ₂ min	dyn. C	stat. Co	min ⁻¹				
	mm					kN		ng grease	ng Oil			
25	25	32	14		1	10.8	15.6	6700		IR 20x25x17	HK 2514RS	0.026
	25	32	16		1	10.8	15.6	6700		IR 20x25x17	HK 2516.2RS	0.031
	25	32	18		1	15.6	25	6700		IR 20x25x20.5	HK 2518RS	0.029
	25	32	20		1	15.6	25	6700		IR 20x25x20.5	HK 2520.2RS	0.032
	25	32	22		1	19.6	34	6700		IR 20x25x26	HK 2522RS	0.042
	25	32	24		1	19.6	34	6700		IR 20x25x26	HK 2524.2RS	0.046
28	28	35	20		1	15.3	25.5	6000		IR 22x28x20.5	HK 2820.2RS	0.042
30	30	37	16		1	11.2	17.3	5600		IR 25x30x17	HK 3016.2RS	0.038
	30	37	18		1	16	28	5600		IR 25x30x20.5	HK 3018RS	0.042
	30	37	20		1	16	28	5600		IR 25x30x20.5	HK 3020.2RS	0.048
	30	37	22		1	21.6	40.5	5600		IR 25x30x26	HK 3022RS	0.050
	30	37	24		1	21.6	40.5	5600		IR 25x30x26	HK 3024.2RS	0.056
35	35	42	16		1	12.9	22	4800		IR 30x35x17	HK 3516.2RS	0.048
	35	42	18		1	16.6	30.5	4800		IR 30x35x20.5	HK 3518RS	0.055
	35	42	20		1	16.6	30.5	4800		IR 30x35x20.5	HK 3520.2RS	0.064
40	40	47	16		1	12.9	23.2	4300		IR 35x40x20	HK 4016.2RS	0.050
	40	47	18		1	18	35.5	4300		IR 35x40x20.5	HK 4018RS	0.058
	40	47	20		1	18	35.4	4300		IR 35x40x20.5	HK 4020.2RS	0.065
45	45	52	18		1	19	39	3800		IR 40x45x20.5	HK 4518RS	0.064
	45	52	20		1	19	39	3800		IR 40x45x20.5	HK 4520.2RS	0.075