



Drawn cup needle roller bearings(imperial sizes)

Series SCE, SCH


BCE, BCH



SCE, SCH



BCE, BCH



BCE, BCH

Shaft diameter	Dimensions			Basic Load Rating		Limiting speeds min ⁻¹	Code bearing HMEC	
	Fw	D	C	Dyn Cr	Stat. Cor		Open end	Closed end
3.175	3.175	6.350	6.350	1070	740	31500	SCE24TN	BCE24TN
3.969	3.969	7.145	6.350	1260	940	25000	SCE2-1/2-4	-
	3.969	7.145	6.350	1230	910	25000	SCE2-1/2-4TN	-
4.762	4.762	8.731	6.350	1790	1360	21000	SCE34TN	BCE34TN
	4.762	8.731	9.525	2750	2350	21000	SCE36TN	BCE36TN
	4.762	8.731	9.530	2800	2440	21000	SCE36	-
6.350	6.350	11.112	6.350	1600	1200	44000	SCE44	BCE44
	6.25	11.112	6.350	1600	1200	44000	SCE44TN	-
	6.350	11.112	7.938	2500	2090	44000	SCE45	BCE45
	6.350	11.112	11.112	4000	3850	44000	SCE47	BCE47
	6.350	11.112	11.112	4000	3850	44000	SCE47TN	-
7.938	7.938	12.700	7.938	2900	2600	35500	SCE55	BCE55
	7.938	12.700	11.112	4700	4850	35500	SCE57	BCE57
	7.938	12.700	14.288	6000	6600	35500	SCE59	BCE59
	7.938	14.288	11.112	4750	4100	29500	SCH57	BCH57
9.525	9.525	14.288	7.938	2900	2700	29500	SCE65	BCE65
	9.525	14.288	9.525	3900	3950	29500	SCE66	BCE66
	9.525	14.288	11.112	4350	4600	29500	SCE67	BCE67
	9.525	14.288	12.700	5800	6600	29500	SCE68	BCE68
	9.525	14.288	14.288	6000	6900	29500	SCE69	BCE69