


**Needle roller bearing inner rings**  
**Series IR**



IR

Shaft diameter	Dimensions				Code bearing	Weight
	d	D	B	r <sub>1</sub> , r <sub>2</sub> min	HMEC	≈ kg
5	5	8	12	0.3	<b>IR 5x8x12</b>	0.003
	5	8	16	0.3	<b>IR 5x8x16</b>	0.004
6	6	9	12	0.3	<b>IR 6x9x12</b>	0.003
	6	9	16	0.3	<b>IR 6x9x16</b>	0.004
	6	10	10	0.3	<b>IR 6x10x10</b>	0.004
	6	10	12	0.3	<b>IR 6x10x12</b>	0.005
7	7	10	10.5	0.3	<b>IR 7x10x10.5</b>	0.003
	7	10	12	0.3	<b>IR 7x10x12</b>	0.004
	7	10	16	0.3	<b>IR 7x10x16</b>	0.005
8	8	12	10	0.3	<b>IR 8x12x10</b>	0.005
	8	12	10.5	0.3	<b>IR 8x12x10.5</b>	0.005
	8	12	12	0.3	<b>IR 8x12x12</b>	0.006
	8	12	12.5	0.3	<b>IR 8x12x12.5</b>	0.006
9	9	12	12	0.3	<b>IR 9x12x12</b>	0.005
	9	12	16	0.3	<b>IR 9x12x16</b>	0.006
10	10	13	12.5	0.3	<b>IR 10x13x12.5</b>	0.005
	10	14	12	0.3	<b>IR 10x14x12</b>	0.007
	10	14	13	0.3	<b>IR 10x14x13</b>	0.007
	10	14	14	0.3	<b>IR 10x14x14</b>	0.008
	10	14	16	0.3	<b>IR 10x14x16</b>	0.009