


**Needle roller bearing inner rings**  
**Series IR**



IR

Shaft diameter	Dimensions				Code bearing	Weight
	d	D	B	r <sub>1</sub> , r <sub>2</sub> min	HMEC	≈ kg
30	30	35	12.5	0.3	<b>IR 30x35x12.5</b>	0.023
	30	35	13	0.3	<b>IR 30x35x13</b>	0.025
	30	35	16	0.3	<b>IR 30x35x16</b>	0.031
	30	35	16.5	0.3	<b>IR 30x35x16.5</b>	0.031
	30	35	17	0.3	<b>IR 30x35x17</b>	0.032
	30	35	18	0.3	<b>IR 30x35x18</b>	0.035
	30	35	20	0.3	<b>IR 30x35x20</b>	0.040
	30	35	20.5	0.3	<b>IR 30x35x20.5</b>	0.041
	30	35	26	0.3	<b>IR 30x35x26</b>	0.050
	30	35	30	0.3	<b>IR 30x35x30</b>	0.059
	30	37	18	0.6	<b>IR 30x37x18</b>	0.050
	30	37	22	0.6	<b>IR 30x37x22</b>	0.061
	30	38	20	0.6	<b>IR 30x38x20</b>	0.065
32	32	37	20	0.3	<b>IR 32x37x20</b>	0.042
	32	37	30	0.3	<b>IR 32x37x30</b>	0.063
	32	40	20	0.6	<b>IR 32x40x20</b>	0.068
	32	40	36	0.6	<b>IR 32x40x36</b>	0.124
33	33	37	13	0.3	<b>IR 33x37x13</b>	0.022
35	35	40	12.5	0.3	<b>IR 35x40x12.5</b>	0.027
	35	40	16.5	0.3	<b>IR 35x40x16.5</b>	0.037
	35	40	17	0.3	<b>IR 35x40x17</b>	0.038
	35	40	20	0.3	<b>IR 35x40x20</b>	0.044
	35	40	20.5	0.3	<b>IR 35x40x20.5</b>	0.046
	35	40	30	0.3	<b>IR 35x40x30</b>	0.068