

HMEC



NA69 (d:32mm)

| Shaft diameter | Dimensions | | | | | Load ratings | | Speed ratings | | Code bearing HMEC | Weight ≈ kg | |
|----------------|------------|-----|----|----------------|----------------|--------------------|----------|----------------------------------|------------------|-------------------|---------------|-------|
| | d | D | B | F ₁ | F ₂ | d _{yn.} C | stat. Co | n _B min ⁻¹ | n _{0.1} | | | |
| mm | | | | | | kN | | rpm | rpm | | | |
| 190 | 190 | 240 | 59 | 210 | 1.5 | 2.5 | 193 | 630 | 1300 | 2000 | NA4838 | 5.86 |
| 200 | 200 | 250 | 59 | 220 | 1.5 | 2.5 | 196 | 655 | 1200 | 1900 | NA4840 | 6.19 |
| 220 | 220 | 270 | 59 | 240 | 1.5 | 2.5 | 208 | 710 | 1000 | 1700 | NA4844 | 6.75 |
| 240 | 240 | 300 | 69 | 265 | 2 | 2.5 | 290 | 1040 | 950 | 1500 | NA4848 | 10.89 |
| 260 | 260 | 320 | 69 | 285 | 2 | 2.5 | 300 | 1120 | 900 | 1500 | NA4852 | 11.60 |
| 280 | 280 | 350 | 69 | 305 | 2 | 3 | 390 | 1270 | 850 | 1400 | NA4856 | 16.70 |
| 300 | 300 | 380 | 69 | 330 | 2.1 | 3.5 | 540 | 1800 | 800 | 1300 | NA4860 | 23.70 |
| 320 | 320 | 400 | 89 | 350 | 2.1 | 3.5 | 540 | 1860 | 750 | 1200 | NA4864 | 25.29 |
| 340 | 340 | 420 | 89 | 370 | 2.1 | 3.5 | 550 | 1930 | 700 | 1100 | NA4868 | 26.70 |
| 360 | 360 | 440 | 89 | 390 | 2.1 | 3.5 | 560 | 200 | 700 | 1100 | NA4872 | 28.00 |