



| Dimensions |        |        | Load rating |             | Code bearing |
|------------|--------|--------|-------------|-------------|--------------|
| d          | D      | B      | dyn.<br>C   | stat.<br>Co | HMEC         |
| mm         |        |        | kN          |             |              |
| 9.525      | 23.019 | 7.938  | 3.33        | 1.41        | <b>1606</b>  |
| 11.112     | 23.019 | 7.938  | 2.69        | 1.27        | <b>1607</b>  |
| 9.525      | 28.575 | 9.525  | 5.11        | 2.39        | <b>1614</b>  |
| 11.112     | 28.575 | 9.525  | 5.11        | 2.39        | <b>1615</b>  |
| 12.7       | 28.575 | 9.525  | 5.11        | 2.39        | <b>1616</b>  |
| 11.112     | 34.925 | 11.112 | 7.45        | 3.70        | <b>1620</b>  |
| 12.7       | 34.925 | 11.112 | 7.45        | 3.70        | <b>1621</b>  |
| 14.288     | 34.925 | 11.112 | 7.45        | 3.70        | <b>1622</b>  |
| 15.875     | 34.925 | 11.112 | 7.45        | 3.70        | <b>1623</b>  |
| 15.875     | 41.275 | 12.7   | 9.39        | 5.02        | <b>1628</b>  |
| 19.05      | 41.275 | 12.7   | 9.39        | 5.02        | <b>1630</b>  |
| 15.875     | 44.45  | 12.7   | 9.39        | 5.02        | <b>1633</b>  |
| 19.05      | 44.45  | 12.7   | 9.39        | 5.02        | <b>1635</b>  |
| 19.05      | 50.8   | 14.288 | 10.06       | 5.86        | <b>1638</b>  |
| 22.225     | 50.8   | 14.288 | 10.06       | 5.86        | <b>1640</b>  |
| 25.4       | 50.8   | 14.288 | 10.06       | 5.06        | <b>1641</b>  |
| 28.575     | 63.5   | 15.875 | 12.30       | 8.53        | <b>1652</b>  |
| 31.75      | 63.500 | 15.875 | 12.30       | 8.53        | <b>1654</b>  |
| 31.750     | 65.088 | 17.462 | 14.90       | 10.04       | <b>1657</b>  |
| 33.338     | 65.088 | 17.462 | 14.90       | 10.04       | <b>1658</b>  |