



**Needle Roller Bearings  
with inner ring  
sealed type  
Series NA49..RS  
NA49..2RS**



NA49..RS



NA49..2RS

Shaft diameter	Dimensions						Load ratings		Speed ratings	Code bearing	Weight
	d	D	B	C	F	$r_{1, f2}$ min	dyn. C	stat. Co	min <sup>-1</sup>	HMEC	≈
	mm						kN		ng grease		kg
10	10	22	13	14	14	0.3	6.6	7.0	10000	<b>NA4900RS</b>	0.027
	22	13	14	14	0.3	6.6	7.0	10000	<b>NA4900.2RS</b>	0.027	
12	12	24	13	14	16	0.3	7.2	8.3	10000	<b>NA4901RS</b>	0.031
	24	13	14	16	0.3	7.2	8.3	10000	<b>NA4901.2RS</b>	0.031	
15	15	28	13	14	20	0.3	8.2	10.4	8500	<b>NA4902RS</b>	0.041
	28	13	14	20	0.3	8.2	10.4	8500	<b>NA4902.2RS</b>	0.041	
17	17	30	13	14	22	0.3	8.5	11	7500	<b>NA4903RS</b>	0.044
	30	13	14	22	0.3	8.5	11	7500	<b>NA4903.2RS</b>	0.044	
20	20	37	17	18	25	0.3	16.3	19.6	6700	<b>NA4904RS</b>	0.087
	37	17	18	25	0.3	16.3	19.6	6700	<b>NA4904.2RS</b>	0.087	
25	25	42	17	18	30	0.3	18.6	24.5	5600	<b>NA4905RS</b>	0.106
	42	17	18	30	0.3	18.6	24.5	5600	<b>NA4905.2RS</b>	0.106	
30	30	47	17	18	35	0.3	19.6	27.5	4800	<b>NA4906RS</b>	0.119
	47	17	18	35	0.3	19.6	27.5	4800	<b>NA4906.2RS</b>	0.119	
35	35	55	20	21	42	0.5	26	41.5	4000	<b>NA4907RS</b>	0.198
	55	20	21	42	0.5	26	41.5	4000	<b>NA4907.2RS</b>	0.198	