



LR 52..KDDU
LR 53..KDD

Outside Dimensions							Load rating		Speed rating	Code bearing	Mass	
diameter d	D	C	B	d ₁	r _{s min}	r _{1s min}	dyn. Cr	stat. Cor	n _D	HMEC	≈ g	
mm							kN		min ⁻¹			
62	20	62	22.2	-	29	1.1	-	21100	14500	6500	LR 5304 KDDU	340
	20	62	22.2	-	29	1.1	-	21100	14500	4500	LR 5304 NPPU	340
68	35	68	20.2	-	41.7	1	-	17600	13100	4300	LR 5007 NPPU	300
72	30	72	23.8	-	37.4	1	-	24600	21400	5000	LR 5206 KDDU	510
	30	72	23.8	-	37.4	1	-	24600	21400	5000	LR 5206 KDD	510
	30	72	23.8	-	37.4	1	-	24600	21400	3500	LR 5206 NPPU	510
72	25	72	25.4	-	34.4	1.1	-	27500	19500	5500	LR 5305 KDDU	500
	25	72	25.4	-	34.4	1.1	-	27500	19500	3900	LR 5305 NPPU	500
80	35	80	27	-	42.4	1.1	-	30500	22400	3900	LR 5207 KDDU	660
	35	80	27	-	42.4	1.1	-	30500	22400	3900	LR 5207 KDD	660
	35	80	27	-	42.4	1.1	-	30500	22400	2800	LR 5207 NPPU	660
	30	80	30.2	-	41.4	1.1	-	36500	26500	4300	LR 5306 KDDU	670
80	30	80	30.2	-	41.4	1.1	-	36500	26500	3100	LR 5306 NPPU	670
	40	85	30.2	-	48.4	1.1	-	34500	25500	3500	LR 5208 KDDU	750
	40	85	30.2	-	48.4	1.1	-	34500	25500	3500	LR 5208 KDD	750
90	40	85	30.2	-	48.4	1.1	-	34500	25500	2500	LR 5208 NPPU	750
	35	90	34.9	-	47.7	1.5	-	44500	33000	3600	LR 5307 KDDU	970
90	35	90	34.9	-	47.7	1.5	-	44500	33000	2500	LR 5307 NPPU	970
	40	100	36.5	-	52.4	1.5	-	56000	42000	3300	LR 5308 KDDU	1200
100	40	100	36.5	-	52.4	1.5	-	56000	42000	2300	LR 5308 NPPU	1200