




HMEC



32... , 33...
contact angle $\alpha \approx 25^\circ$



32...ZZ, 33...ZZ, 38...ZZ



32...2RS, 33...2RS, 38...2RS

Shaft diameter	Dimensions					Load rating		Limiting speed	Reference speed	Code bearing	Mass
	d	D	B	$r_{s \min}$	a°	dyn. C	stat. Co				
	mm					\approx kN	min^{-1}			HMEC	\approx kg
20	20	47	20.6	1	24	19.6	12.5	8500	-	3204 2RS	0.158
	20	52	22.2	1.1	26	23.2	15	13000	11000	3304	0.217
	20	52	22.2	1.1	26	23.2	15	9000	11000	3304 ZZ	0.222
	20	52	22.2	1.1	26	23.2	15	8000	-	3304 2RS	0.221
	20	32	10	0.3	14.3	5.6	4.85	13000	13000	3804 2RS	0.02
	20	32	10	0.3	14.3	5.6	4.85	13000	13000	3804 ZZ	0.02
25	25	52	20.6	1	26	21.2	14.6	12000	14000	3205	0.178
	25	52	20.6	1	26	21.2	14.6	8500	14000	3205 ZZ	0.182
	25	52	20.6	1	26	21.2	14.6	7500	-	3205 2RS	0.182
	25	62	25.4	1.1	31	30	20	10000	10000	3305	0.353
	25	62	25.4	1.1	31	30	20	7500	10000	3305 ZZ	0.359
	25	62	25.4	1.1	31	30	20	6700	-	3305 2RS	0.359
	25	37	10	0.3	15.9	6.0	5.6	11500	11500	3805 2RS	0.025
	25	37	10	0.3	15.9	6.0	5.6	11500	11500	3805 ZZ	0.025
30	30	62	23.8	1	31	30	21.2	9500	12000	3206	0.289
	30	62	23.8	1	31	30	21.2	7000	12000	3206 ZZ	0.295
	30	62	23.8	1	31	30	21.2	6300	-	3206 2RS	0.296
	30	72	30.2	1.1	36	41.5	28.5	8500	9000	3306	0.548
	30	72	30.2	1.1	36	41.5	28.5	6300	9000	3306 ZZ	0.558
	30	72	30.2	1.1	36	41.5	28.5	5600	-	3306 2RS	0.558
	30	42	10	0.3	32.8	6.3	6.1	10000	9500	3806 2RS	0.03
	30	42	10	0.3	32.8	6.3	6.1	10000	9500	3806 ZZ	0.03